

Rhepanol Membrane Guarantee Table - Jan 2010



			10 Years		15 Years		20 Years	
			Warm Roof	Inverted Roof	Warm Roof	Inverted Roof	Warm Roof	Inverted Roof
Exposed / visible	Mechanically fixed with Gripfix	Rhepanol fk With achieved 1:80 falls	✓		✓		✓	
		Rhepanol fk Less than 1:80 falls	✓ (1)		✓ (1)			
	Bonded	Rhepanol fk With achieved 1:80 falls	✓		✓		✓	
		Rhepanol fk Less than 1:80 falls	✓ (1)		✓ (1)			
Non exposed / visible	Ballasted	Rhepanol fk With achieved 1:80 falls	✓ (2)		✓ (2)			
		Rhepanol fk Less than 1:80 falls	✓ (2)		✓ (2)			
		Rhepanol hg With achieved 1:80 falls	✓	✓	✓	✓	✓ (3)	✓ (3)
		Rhepanol hg Less than 1:80 falls	✓ (3)	✓ (3)				

✓ (1) Note: Where achieved falls are below 1:80 the application of two coats of Rhepanol copper paint or 20 - 40 riverwashed ballast is required.

✓ (2) Note: Protection layer min 300 g/m² fleece is required below paving pad supports, pneumatically applied or non standard gravel ballast. FDT protection layer with welded seams is required below screed bedding.

✓ (3) Note: Minimum thickness of hg 1.8 not 1.5mm

Written project guarantees are only available to members of the Design and Technology Accredited Contractors Scheme (DATAAC). Details to join can be found at www.accreditedcontractors.co.uk