



Apollo Chemicals Limited,
 Sandy Way, Amington Industrial Estate, Tamworth, Staffs. B77 4DS.
 Telephone: +44 (0) 1827 54281
 Facsimile: +44 (0) 1827 53030 www.apolloadhesives.com email: sales@apolloadhesives.com

BASE Solvent	TECHNICAL DATA SHEET SOLVENT MEMBRANE SEAM CLEANER	PRODUCT A3684
SOLIDS N/A	Apollo A.3684Seam Cleaner is used to clean PVC or TPO roof membranes prior to welding. It can also be used as a general cleaner to remove residual dirt and wet adhesive from roof membranes.	
VISCOSITY 1.73 cst @ 40°C	PROPERTIES Density 0.8 g/cm ³ Boiling range 185 - 260°C Aromatic Content 0.3% vol. Benzene Content Nil Naphthene Content Nil	
COLOUR Clear		
TACK LIFE N/A		
COVERAGE N/A		
CLEANER N/A		
FLASH POINT 77°C (pmcc)		
SHELF LIFE 12 months	CONTINUED OVER PAGE	



Ref : A 3684	Date : 25/09/06
--------------	-----------------

The above figures do not constitute a specification. They represent typical values obtained for this product.

HEALTH AND SAFETY

Before using this product please ensure that you have been supplied with and have read carefully the following information:

1. The hazard labels (complying with CHIP and CDG/CPL Regs).
2. Apollo Material Safety Data Sheet A3684

IMPORTANT NOTICE

This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. All recommendations and suggestions are therefore made without guarantee. Samples will be provided on request to enable customers to satisfy themselves as to the suitability of the product for any specific purpose and to assess the product under their own working conditions.